

Engage consumers. Offer multiple payment options. One device for cash & cashless.

Part of Nayax's cashless payment solution for unattended automated machines Complete management and telemetry suite Reports & real-time data gathering capabilities Easy navigation with color touchscreen ACCEPTS Consumer engagement tools CASH Features bill validator support SAMSUNG **É**Pay **G**Pay VISA Ġ Paytr 🐼 τωιοτ pay MobilePav Felica Certified **DISC** EMVCo 微信支付 Part of a complete solution **Reporting capabilities**

A card reader with cash options, cashless clearance, telemetry & monitoring, and remote management

Boosts revenue

2

- More payment choices increase sales
- Credit and debit cards swipe, contact & contactless
- Mobile apps, QR codes and prepaid cards

Cash capabilities

- Combo bezel for bill validator
- Track cash collections
- Cash accountability

- Real-time data transmission
- Inventory and cash monitoring, alerts & reports
- Continuously updated information on all aspects of operation

Communicate with your consumers

- ▶ Voice interaction, in local language
- Multiple language display capacity
- Customizable color touchscreen

Dynamic marketing tools


Promote your business

6

- Develop customer loyalty with promotions
- Offer punch cards & loyalty discounts
- Advertise via color touchscreen







A complete payment solution for unattended automated machine operators

Benefit from easy installation, clearance, monitoring, cash accountability and management

Interface & Management		
Display Screen	Color Touch LCD Display 2.4 inch IPS 320 x 240 Pixels + 4 LEDs + 6 soft touch buttons	
Voice	Speaker + Buzzer	
Power Supply	Operating Voltage: DC 12-40V, AC - Option Power < 10 Watt From Vending Machine	
Power Consumption	From vending machine Max: 400mA @ 24V DC ; Recommended External Power Supply ; 24V DC / 2Amp.	
RF Contactless Interface	Frequency - 13.56 MHz, MIFARE, NFC, HID	
Security	Support of DES, 3DES, AES, RSA, SHA1 algorithms, Random Number Generator	
External Interface	Mini USB (Host/Device), Ethernet ; Internal Flash 64MB+32MB, Micro SD Card, SDRAM 32MB ; Optional: Bluetooth & WiFi	
Antenna	Frequency = 13.56 MHz Operation Temperature = -20°C to 85°C Humidity = Non Condensing 65°C 95% RoHS compliant	
Glass	Anti-Vandal with Dragontrail Glass	
RS232	2 * RS232 TTL level manageable (software)	
Pulse Input/Output	6 in/out interfaces + 1 input (Inhibit)	
External Sensors	1 Door open & 1 Temperature	
Communication	2G / 3G / 4G / Ethernet / NFC	
Machine Protocols	MDB (+DEX/DDCMP) / Pulse / VCCS / ccTalk / JVMA	

Payment Support

Contact	100,000 insertion cycles EMV Level 1 - Certified EMV Level 2 4.3f -All Visa, MC, JCB, AmEx, CUP	Contactless	Visa PayW MasterCa JCB - J/Sp
Magnetic Stripe	ISO 7811 and JIS I Tracks 1,2,3 ; JIS II		Discover I
Other Cards Supported	NFC, MIFARE, HID-iClass	Cash	Cash acce

Contactless	Visa PayWave 2.1.3b MasterCard PayPass 3.1.1 JCB - J/Speedy 1.3 Discover D-Pass 1.0	
Cash	Cash acceptance via a third party bill validator	

Installation Environment			
Operating Temperature	-20°C to 55°C / -4°F to 131°F		
Storage Temperature	-30°C to 85°C / -22°F to 185°F		
Humidity	25% to 95% (non-condensing)		
Dust & Water Resistance	IP 55		
Flammability	V-0 3MM UL-94 V0		

Warranty	
Time Frame	2 years

Let Nayax help your business maximize your profits. Contact us today to learn more.

www.nayax.com