

AquaCafé® CT

Single Serve POD Coffee & Tea



Features

- 0.8L / 0.21G stainless steel hot tank
- 40,000 cycles Commercial Grade components
- Single-serve soft POD coffee & tea in about 45 seconds
- Brew sizes and brew temperature user defined
- Counter top model either pour-over tank or plumbed in
- Easy Touch Screen interface
- One touch dispensing of hot water
- Simple three-step brewing process — (1) insert pod, (2) select cup size, and (3) press brew
- Secondary fold-down drip tray accommodates a variety of container shapes and sizes
- Auto eject of PODS — no touching of used pods
- Integrated trash bin holds up to 30 used pods
- Energy Save and Sleep Modes
- Available in black
- UL listed

Why Single Serve POD Coffee?

- Superior Flavor and Robustness
- Up to 12 grams of Fresh Ground Coffee
- Higher Brew Temperature for Superior Extraction
- No Residual Plastic Taste in Your Beverage
- Environmentally Responsible
- Compostable. Decomposes in Landfills
- No Product Losses from Employee Home Consumption
- Distributor has Better Control of POD Supply



www.avskompanies.com
(847) 439-9400 | sales@avskompanies.com



Power

Voltage	120V
Frequency (Hz)	60
Total Power Consumption	12.5A / 1500W / 120V
Total Power Consumption (AH)	11.5A / 1305W / 115V

Hot Water System

Avg. Hot Water Temp at Nozzle @ 75°F Ambient	172°F / 190.4°F
Brewing Temperature	194°F Maximum 205°F
Hot Water ARI Rating	45, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	221°F (Safety)
Hot Thermostat / Thermistor Cycle	215.6°F - 226.4°F
Hot Water Flow Rate	0.18 oz./sec
Hot Tank Size (Liter : Gallon)	0.8L : 0.21G
Hot Tank Material	304 Stainless Steel

Weights and Measurements

Net Weight (Lbs.)	21.16
Gross Weight (Lbs.)	23.8
Max Distance from Drip Tray to Faucet (Adjustable) (Inch : mm)	7.56 : 192.02
Cooler Dimensions WxDxH (inch : mm)	11.53 x 17.71 x 15.51 : 292 x 449 x 393
Boxed Dimensions WxDxH (inch : mm)	20.47 x 14.8 x 19.29 : 519 x 375 x 489
Container Load (20')	308
Container Load (40')	636
Container Load (40' HC)	720
Container Load (45' HC)	810
Certifications	UL Listed, Energy Star Rated
Model Number	ACB 520p

Warranty:

2 years: Parts (electrical to include cold controls, relay overloads and PCB's)