

# AquaCafé®

## AquaCafé® POD Bottled Water or Filtration Cooler



## Features

- Single-serve coffee & tea in about 45 seconds, and hot & chilled water for residential and small offices
- Hotter water for barista quality coffee, tea, and for cooking instant noodles and soups
- Space saver — frees up counter space, no brewer or coffee pot on the counter or filtration system at the sink
- Time saver — Barista quality coffee brewed at home or office. No drive to expensive coffee house or waiting in line
- Brews 6, 8, 10, 12, and 14 ounce cup sizes
- Safety lock function for hot water
- Easy-to-use touch screen with illuminated dispensing area and brightness controls
- Adjustable drip tray that is removable for easy cleaning
- 1L / 0.28G stainless steel hot tank
- 3.78: / 1G cold tank
- Bottled water models load from the bottom so there is no lifting of heavy bottles — just slide into place
- Filtration models have room inside for single or dual icon eco3 filters or an RO system
- Sealed controls keep out dirt and liquid
- **Accu-Temp™** — Serves water at the proper temperature very time
- **Stay-Cool®** — Keeps residual water in the cold waterway chilled and ready to serve
- UL listed

### Power

Voltage	115V
Frequency (Hz)	60
Total Power Consumption	1300W
Cold Power Consumption	100W
Hot Power Consumption	1200W

### Brewer Hot Water System

Avg. Hot Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	194°F / 201.2°F
Hot Thermometer / Heat Limiter	221°F
Hot Thermostat / Thermistor Cycle	194°F - 201.2°F
Hot Tank Size (Liter : Gallon)	1L : 0.26G
Heating Element	Internal Heating Element

### Hot Water System

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	174.38°F / 194.9°F
Hot Water ARI Rating	121, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	221°F
Hot Thermostat / Thermistor Cycle	Cut-in: 72.4°F Cut-out: 190.4°F
Hot Water Flow Rate	0.49oz./sec
Heating Element	Internal Heating Element

### Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	45.7°F / 43.88°F
Cold Water ARI Rating	18, 5 oz. > 50°F +/- 10%
Cold Thermostat Set Point	Cut-in: 50°F Cut-out: 45°F
Cold Water Flow Rate	1.073 oz./sec
Cold Tank Size / Usable Volume(Liter : Gallon)	3.8 / 2.8 / 1.51 : 1 / 0.74

### Weights and Measurements

Net Weight (H&C / C&C Lbs.)	37.48
Gross Weight (H&C / C&C Lbs.)	43.3
Max Distance from Drip Tray to Faucet (Adjustable) (Inch : mm)	8.75 : 222.25
Faucet / Dispense Height (Inch : mm)	37.5 : 952.5
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	17.04x14.09x43.5 / 17.52x14.76x45.67

### Filter Compartment Dimensions

Width (Inch : mm)	12 : 304.79
Depth (Inch : mm)	11 : 279.4
Inside Top to Bottom (Inch : mm)	21.75 : 323.85
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45' HC)	518

### Warranty:

3 years: Sealed refrigeration system

2 years: Parts (electrical to include cold

controls, relay overloads and PCB's)

Inspirations trademark owned by Aquabeve. ©2018 Aquabeve. All rights reserved 09/2018

Certifications UL Listed

Models (BW : Filtration) ACB 210r-P: ACB215 r-P