



# HEALTH & SAFETY COOLER



# ABOUT COOLBLU

The CoolBlu Cooler deploys a world class control system allowing the user to use the cooler as a food cooler or beverage cooler. State of the art locking system is simply programmed to turn on/off through the control system. This eliminates the need for different types of coolers. CoolBlu can do it all.

NAMA certified, this cooler has built in Bluetooth Technology with the ability to track number of door openings, length of time the cooler has been without power, time between last power cycles and finally, the maximum temperature inside the cabinet. Telemetry is also an option with CoolBlu.



### Electronic Fan Motors

Reliable, high-performance fan that uses less power and last longer.



### Intuitive LED Lights

LED uses the lowest energy available as well as indicating the coolers health lock status.



### CFC & HFC Free Insulation

Eco-Friendly insulation creating an environmentally friendly cabinet.



### Electronic Thermostat

An electronic temp controller that makes for a worry-free cabinet.



### Efficient Glass Door

Self closing swing door with unique pin spring.



### Noise Level

Operating at 52.3 dB

## Maintenance Simple

- Slide in/out refrigeration cassette deck for ease of cleaning and replacement.
- Hidden controls for adjusting Temperature
- UL listed and designed for low power consumption
- LED shield protects packaged food

## Door & Cabinet

- One piece foamed cabinet offering maximum structural strength
- Easily reversible door to meet location requirements\* (Beverage Application Only)
- Interior NSF certified white or black liner
- Standard 5 white coated shelves



Front Visible Temp



CoolBlu Refrigeration Module

# COOLER OPTIONS



Model Numbers	Description
ACB305FDP	CoolBlu Cooler Full Glass Door Propane
ACB305HDRP	CoolBlu Cooler w/ Header Propane
ACB305FDBP	CoolBlu Cooler Full Glass Door Black Interior Propane
ACB305HDRBP	CoolBlu Cooler w/ Header Black Interior Propane

DIMENSIONS		ELECTRICAL		THERMOSTAT SETTING <i>(default)</i>	
Internal (W/D/H) in.	<b>27" x 29" x 60"</b>	Power Supply	<b>115V 60 Hz</b>	Cut-Out/Cut-In	<b>34° F/41° F</b>
External (W/D/H) in.	<b>30" x 32" x 79.5"</b>	Amps	<b>3.0</b>		
Weight (lbs)	<b>375</b>	Lighting	<b>LED</b>		
REFRIGERATION		CAPACITY		VOLUME	
Refrigerant	<b>R290</b>	Shelves	<b>5</b>	Cubic Feet	<b>27</b>
Compressor Power	<b>1/3 HP, 380 Watts</b>	Facing 20 oz. PET/Shelf	<b>9x5</b>		
Energy Consumption	<b>2.37 kWh/day</b>	Total Facing (20 oz PET)	<b>45</b>		

## Available Options:

### Food Trays:

Part #2031279

### Shelving:

White Shelf #HAC2072

Black Shelf #HAC2072B

### Product Glides:

Gravity Part #861715101


Spring Part #861715001



## CONTACT US

Premium Product Group, LLC

 750 Morse Avenue  
Elk Grove Village, IL 60007

 847-709-6299

 [info@premiumproductgroup.com](mailto:info@premiumproductgroup.com)

 [www.premiumproductgroup.com](http://www.premiumproductgroup.com)